

Vinyl Primer Spray

Product description

Type

This is a one component physically drying vinyl sealer/primer. It is fast drying.

Features and benefits

Pigmented with a high content of aluminium flakes giving good waterproof protection. Gives excellent adherence to antifouling. Supplied in a spray can for easy application.

Recommended use

To be used on drives, flaps, propellers and light metal parts below the waterline. Specially designed as preparation for Aqualine antifouling supplied in a spray can.

Product data

Packaging (typical):	Volume (litres)	Size of containers (litres)
Vinyl Primer Spray	0.4	0.4

The volume stated is for factory made colours. Note that local variants in pack size and filled volumes can vary due to local regulations.

Base availability

Solids by volume:	38 ± 2 volume%
Flash point:	-7 °C
VOC:	615 g/l US EPA method 24

The provided data is typical for factory produced products, subject to slight variation depending on colour.

Application data

Product mixing ratio (by volume)

Film thickness and spreading rate per coat

Typical recommended specification range

Wet film thickness	80 – 105	µm
Dry film thickness	30 – 40	µm
Theoretical spreading rate	12.7 – 9.5	m ² /l

Thinner/Cleaning solvent

Drying and Curing time

The drying time is measured by stated values:

Substrate temperature	5 °C	10 °C	23 °C	40 °C
Surface (touch) dry	30 min	20 min	15 min	10 min
Hard dry / Walk-on-dry	4 h	3 h	2 h	1.5 h
Recoatable, minimum	4 h	3 h	2 h	2 h

Surface (touch) dry: The state of drying when slight pressure with a finger does not leave an imprint or reveal tackiness.

Hard dry / Walk-on-dry: Minimum time before the product can tolerate normal foot traffic without permanent marks, imprints or other physical damage.

Recoatable, minimum / Dried to over coat, minimum: The recommended shortest time before the next coat can be applied.

Directions for use

Shelf life at 23 °C

Vinyl Primer Spray 48 month(s)

In some markets commercial shelf life can be dictated shorter by local legislation. The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

Disposal of waste

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not inhale spray mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

Product registration number: 2493276

Safety rules

4-6

1993

Colour variation

When applicable, products primarily meant for use as primers or antifouling may have slight colour variations from batch to batch. Such products may fade and chalk when exposed to sunlight and weathering.

Colour and gloss retention on topcoats/finish coats may vary depending on type of colour, exposure environment such as temperature, UV intensity etc., and application quality. Contact your local Jotun office for further information.

Miscellaneous

Contact information

Jotun Danmark A/S
Jernet 6
6000 Kolding
Tlf.: +45 76 30 32 00
Mailadresse: mail@jotun.dk

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.